

Xerox® DocuMate® 4790 Scanner

Reliable High-Speed Scanner Increases Office Efficiency

- 70 ppm / 140 ipm* at 300 dpi
- A3 (11" x 17") paper size
- ADF holds 200 pages†
- LCD Front Panel for job control, status and alerts
- Ultrasonic double feed detection sensor
- Create searchable PDF files to make it easy to find scanned documents
- Pre-Imprinter (sold separately)
- Color Space Compatibility with Xerox® iGen® digital press
- Xerox® FreeFlow Makeready® Supported

* Landscape US letter and A4, b&w, gray & color.
† 20 lb., 75-80 g/m² paper



EQUIPMENT YOU CAN DEPEND ON

The Xerox® DocuMate® 4790 is the ideal scanner for both large-volume and distributed scanning environments. It has a duty cycle of up to 15,000 sheets per day and has been engineered with innovative features for easy operation and productive batch scanning, including ultrasonic double feed detection and support for long document scanning.

A highly reliable and compact document scanner, the Xerox® DocuMate® 4790 scans up to 90 ppm and 180 ipm and includes a 200-page Automatic Document Feeder that accepts up to A3 (11" x 17") size documents and can handle nearly any mix of paper in various sizes and thicknesses. Its unique paper feed mechanism minimizes the possibility of damaging important documents and ensures precise feeding to make your office work even more efficient. The roller is designed for efficiency by separating itself from the page each time a sheet is fed, reducing the likelihood of drag and double feeds, and improving the useful life of the roller. A separate double feed prevention roller applies controlling pressure when paper 'sliding' (caused by buildup of toner or carbon on the rollers) is detected.

The scanning glass is protected by the use of various sensors that detect stapled pages and automatically interrupt the scan process. It is also equipped with ultrasonic multi-feed detection and a function that removes dust from the scanning glass to ensure consistently high image

quality. The Xerox® DocuMate® 4790 has a convenient clamshell design that allows direct and straightforward access to the entire paper path, so a user can clear paper jams, clean the unit, or replace rollers easily without having to call a service technician. A pre-scan imprinter is also available for the Xerox® DocuMate® 4790 and is supported through the included TWAIN™ and ISIS® drivers.

INTUITIVE TOOLS AND DESIGN

The Xerox® DocuMate® 4790 provides both high-quality image enhancement and increased productivity with Kofax® VRS™ Professional AIPE-EBC for auto-everything scanning, including Auto Rotation, Blank Page Deletion and Auto Color Detect. VRS Professional improves your workflow and reduces the total time required to finish even the largest batches of mixed documents. TWAIN and ISIS drivers are included to ensure compatibility with document management software and your capture applications. The DocuMate 4790 is powered by Visioneer® OneTouch® scanning technology for simplifying scan jobs and workflow. The scanner also has an easy-to-read LCD on the front that reminds the user of the resolution, color mode, file type, processing and final destination of the scanned document.

You'll find the Xerox® DocuMate® 4790 to be the kind of advanced and reliable equipment you expect to come from Xerox. We wouldn't have it any other way.

Xerox® DocuMate® 4790 Software Solutions

VISIONEER® ACUITY

Visioneer Acuity with DriverPLUS technology enables your scanner to instantly improve the visual clarity of scans. On the DocuMate 4790, fifteen Acuity features are onboard, which means it is built into the scanner hardware, thus saving CPU power and keeping you scans going at full speed. Using advanced algorithms Acuity intelligently corrects documents containing imperfections, increases OCR accuracy, and improves the quality of scanned images for archiving.

VISIONEER ONETOUCH®

Visioneer OneTouch is an easy-to-use scanning utility that sends your scanned documents to nearly any destination by simply pressing a button on your Xerox® DocuMate® scanner. The scanned files are automatically delivered to a folder, email, Microsoft Office application, a local or network printer, or create a custom workflow. OneTouch is integrated with Visioneer Acuity so the image enhancement features are all available with the simplicity of one button scanning.

VISIONEER TWAIN DRIVERPLUS

DriverPLUS offers an impressive array of settings to enable precise customization of the scan – far beyond current TWAIN specifications and user experience. DriverPLUS also delivers Parallel Scanning, allowing multiple same-model scanners to be connected to a single PC and run concurrent jobs. Visioneer Acuity integration adds intelligent image enhancement and PC Optimization to enable full-speed scanning.

ABBY® FINE READER SPRINT

This easy-to-use OCR tool reduces the need of retyping and paper storage, instantly converting your scans into various file formats, including searchable PDF. It accurately reads documents in up to 179 languages and precisely preserves the original document's layout and formatting.

For more information about the Xerox line of scanners, visit www.xeroxscanners.com



Xerox® DocuMate® 4790 Product Specifications	
Model Number w/VRS Pro(US)	XDM 47905D-WU
Model Number w/VRS Basic (US)	XDM47905D-VRS/B
Model Number w/VRS Pro(Euro/UK)	XDM 47905E-WU
Model Number w/VRS Basic (Euro/UK)	XDM47905E-VRS/B
Scan Speed	90 ppm / 180 ipm (black & white, grayscale, or color at 200 dpi, landscape on A4, 8.5" x 11" US letter paper)
	70 ppm / 140 ipm (black & white, grayscale, or color at 300 dpi, landscape on A4, 8.5" x 11" US letter paper)
Scan Method	Automatic Document Feeder (ADF)
Imaging Sensor	Dual Charge-Coupled Device (CCD)
Light Source	White LED light source
Background	Switchable black or white background
Optical Resolution	600 dpi
Output Bit Depth	24-bit color, 8-bit grayscale, 1-bit black & white
Other Functions	Length control, barcode detection, patch code detection, Automatic separation, control sheet, long paper mode
Interface	Hi-speed USB 2.0 (1.1 compatible)
Detection	Ultrasonic double feed detection, stapled document detection
Accessories	DocuMate 4700 flatbed scanner, Pre-Imprinter
ADF Minimum Document Size	1.9" x 2.8" (48 mm x 70 mm)
ADF Maximum Document Size	12" x 17" (305 x 432 mm); Custom sizes up to 12" x 100" (305 x 2540 mm)
ADF Capacity	200 sheets (20 lb., 75-80 g/m ² paper)
ADF Paper Thickness Range	5 - 42 lbs. (19 - 157 g/m ²) (auto)
Document Thickness	1.6 - 7.9 mils (0.04 - 0.2 mm) Note: 1 mil = 0.001".
Duty Cycle	15,000 pages/day
Power Requirement	AC 100 – 240 V, 50/60 Hz
Power Consumption	Maximum (Scanning) 100 watts
	Minimum (Standby) 35 watts
	Sleep Mode 3.5 watts or less
Operating Environment	Temperature: 59°F - 86°F (15°C - 30°C)
	Humidity: 20 - 80% RH
Storage Environment	Temperature: 32°F - 104°F (0°C - 40°C)
	Humidity: 10 - 80% RH
Dimensions	18.5"(w) x 17.5"(d) x 13.4"(h) (468 x 444 x 339 mm)
Weight	40 lbs. (18 kg)

BOX CONTENTS

- DocuMate 4790 Scanner
- Quick Installation Guide
- Technical Support Card
- Blower w/Brush
- Roller Cleaning Paper, Cleaning Paper Card
- Shading Sheet, Shading Caution Leaflet
- DFP (Double Feed Protection) Roller
- AC Power Cord US (1), Euro/UK (2)
- USB Cable
- DVD-ROM including:
 - User's Manual
 - Kofax VRS Pro (with AIPE-EBC) or with VRS Basic depending on SKU*
 - Visioneer OneTouch
 - Visioneer Acuity
 - ABBYY Fine Reader Sprint
 - Scanner Drivers: TWAIN™, EMC Captiva ISIS®, Microsoft® Windows® Image Acquisition (WIA) Driver, Visioneer DriverPLUS

PC MINIMUM SYSTEM REQUIREMENTS

- Intel® Pentium® 4 or equivalent processor
- Compatible with:
 - Windows® 10 Pro, Home, Enterprise and Education
 - Windows 7 Pro, Home, Enterprise and Ultimate
 - Windows 8/8.1 Pro, Core and Enterprise
- 2GB RAM
- 350 MB available hard disk space
- DVD-ROM drive
- USB port

CONSUMABLES:

- 4790ROLL-KIT - User installable roller assembly. Up to 350,000 scans.

* Kofax VRS 4.5 is not supported on Microsoft Windows 8

©2019 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, DocuMate®, FreeFlow Makeready® and iGen® are registered trademarks of Xerox Corporation in the United States and other countries, and are used under license from Xerox Corporation. Visioneer® is an authorized trademark licensee of Xerox®. Visioneer® and Visioneer OneTouch® are trademarks of Visioneer, Inc. Kofax®, VirtualReScan® and VRS™ are trademarks of Kofax, Inc. Microsoft® and Windows® are trademarks of Microsoft Corporation in the United States and/or other countries. Intel® and Pentium® are trademarks of Intel Corporation in the U.S. and/or other countries. ABBYY®, ABBYY® FineReader and FineReader are either registered trademarks or trademarks of ABBYY Software Ltd. TWAIN™ is a trademark of TWAIN Working Group. EMC®, Captiva®, and ISIS® are trademarks of EMC Corporation. ENERGY STAR® and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. Universal Serial Bus is a trademark of USB Implementers Forum, Inc. (USB-IF). All other trademarks are the property of their respective owners and are hereby acknowledged. Prices, features, specifications, capabilities, appearance and availability of Xerox® products and services are subject to change without notice. 06/19 BR24395

