Xerox[®] DocuMate[®] 4799 Scanner A3 Production Scanner

Extra Performance and Versatility for Heavy Scanning Demands

Features:

- Up to 112 ppm / 224 ipm* at 300 dpi
- A3 (11" x 17") paper size
- ADF holds 350 pages⁺
- 3 Ultrasonic double feed detection sensors
- Create searchable PDF files to make it easy to find scanned documents
- Pre- & Post-Scan Imprinter (sold separately)
- Colour Space Compatibility with Xerox[®] iGen[®] digital press
- Xerox[®] FreeFlow Makeready[®] supported

* Landscape A4, b&w, grey & Colour. † 20 lb., 75-80 g/m² paper



Document Manager Magazine's 2015 Product of the Year, and 2016 High Volume Imaging Product of the Year.



OVERCOME YOUR FEAR OF DIFFICULT DOCUMENTS

Versatility, high-speed and superior reliability make the DocuMate 4799 a powerful scanner for demanding environments. With up to a 40,000 page per day duty cycle, this innovative workhorse scans up to 112 pages per minute and employs three advanced sensor systems: ultrasonic double feed detection, stapled document detection and intelligent feed control to ensure that your scan job will not get interrupted.

Documents of various sizes can be stacked together in the automatic feed tray without worry because the DocuMate 4799 employs not one, but three ultrasonic double feed detection sensors to cover the entire width of a document. The scanner has another set of sensors designed to detect staples anywhere in a document. As soon as a staple is detected, the scanning process is halted—minimizing damage to the optical glass and your documents. A third set of sensors constantly monitors the thickness of documents being fed into the scanner and automatically adjusts the roller pressure to ensure that all pages are accurately fed. This combination of sensors creates one of the most reliable feed mechanisms available today.

Up to 350 mix-sized documents can be stacked in the center of the automatic feeder. There is no need to organize documents according to their size, so scanning is fast, easy and efficient. A preand post-scan imprinter is also available for the DocuMate 4799 and is supported through the included TWAIN[™] and ISIS[®] drivers.

ADVANCED IMAGE PROCESSING TECHNOLOGY

The DocuMate 4799 provides both high quality image enhancement and increased productivity with Kofax[®] VRS[™] Professional AIPE-EBC for auto-everything scanning, including Auto Rotation, Blank Page Deletion and Auto Colour Detect. VRS Professional improves your workflow and reduces the total time needed to scan even the largest volumes of mixed batch documents. Taken together, the DocuMate 4799 and the Kofax VRS Professional bundle translate into real and measurable savings—fewer manual steps, reduced storage requirements and less operator intervention.

When the occasional paper jam happens, the DocuMate 4799 is very easy to maintain. Its unique "clamshell" design allows full access to the entire paper path, so you can clear paper jams or clean the unit without calling a service technician. The rollers are easy to replace, improving the unit's cost effectiveness, and have a long service life.

Designed for document capture and workflow the DocuMate 4799 is everything you ever wanted in a high-speed document scanner: productivity, reliability and innovation.



VISIONEER INTELLIGENT SOFTWARE PLATFORM FOR WINDOWS

OneTouch

Acuity

Capture SE

An easy-to-use scanner workflow application that performs all steps in a complex scanning operation at the touch of a button. Enables you to improve the visual clarity of scans. Acuity uses over 25 advanced algorithms to intelligently correct documents. Flexible, powerful batch scanning solution that can split scans into separate files, create indexes, read barcodes and extract data.

DriverPLUS

Provides an impressive array of settings to enable precise scan customization with a simple-to-use interface and helpful tool tips.

Organizer AI

Manages your files with fast search, conversion, file analysis and cleanup, tagging, PDF editor and automated file classification.

ADDITIONAL SOFTWARE

ABBYY® Software: ABBYY FineReader OCR Software Kofax® VRS™ Software: Kofax VRS Pro (with AIPE-EBC) or with VRS Basic depending on SKU* Scanner Drivers for Windows: TWAIN™, ISIS®, WIA

* Kofax VRS 4.5 is not supported on Microsoft Windows 8 and higher

Model Number w/VRS Pro (Euro/UK)	XDM47995E-WU	100N02782	
Model Number w/VRS Basic (Euro/UK)	XDM47995E-VRS/B	100N02825	
Scan Speed	Up to 112 ppm / 224 ipm (Colour, G	Up to 112 ppm / 224 ipm (Colour, Greyscale, or b&w @ 150, 200, or 300 dpi, landscape A4)	
Scan Method	Automatic Document Feeder (ADF)	Automatic Document Feeder (ADF)	
Image Sensor	Dual Colour CIS detector	Dual Colour CIS detector	
Light Source	LED	LED	
Optical Resolution	600 dpi	600 dpi	
Output Bit Depth	24-bit Colour, 8-bit Greyscale, 1-bit t	24-bit Colour, 8-bit Greyscale, 1-bit black & white	
Other Functions	Length control, barcode detection, p long paper mode	Length control, barcode detection, patch code detection, Automatic separation, control sheet, long paper mode	
Background	Switchable black or white backgrour	Switchable black or white background	
Detection	Ultrasonic double feed detection (3	Ultrasonic double feed detection (3 positions), stapled document detection	
Interface	Hi-speed USB 2.0	Hi-speed USB 2.0	
ADF Minimum Document Size	48 mm x 70 mm (1.9" x 2.8")		
ADF Maximum Document Size	302 × 432 mm (11.9" x 17"); custom	302 × 432 mm (11.9" x 17"); custom lengths up to 2540 mm (100")	
ADF Paper Thickness Range	5 – 42 lbs. (19 ~ 157 g/m2) (auto)	5 – 42 lbs. (19 ~ 157 g/m2) (auto)	
Document Thickness	0.04 – 0.2 mm (1.9 – 7.9 mils) Straight path: max. 23.6 mils (0.6 mm) Note: 1 mil = 0.001"		
ADF Capacity	Up to 350 sheets (20 lb., 75-80 g/m ² paper)		
Power Requirement	AC 100 – 240 V, 50/60 Hz	AC 100 – 240 V, 50/60 Hz	
Power Consumption	150 watts while scanning		
	50 watts in Ready / Waiting Mode	50 watts in Ready / Waiting Mode	
	2 watts or less in Sleep Mode		
Operating Environment	Temperature: 15°C – 30°C (59°F – 86	Temperature: 15°C – 30°C (59°F – 86°F)	
	Humidity: 10 – 80 % RH		
Storage Environment	Temperature: 0°C – 40°C (32°F – 104	Temperature: 0°C – 40°C (32°F – 104°F)	
	Humidity: 30 – 80 % RH	Humidity: 30 – 80 % RH	
Scanner Dimensions (W x D x H)	474 x 585 x 329 mm (18.7" x 23" x 2	474 x 585 x 329 mm (18.7" x 23" x 13")	
Weight	25 kg (55 lbs.)	25 kg (55 lbs.)	
Duty Cycle	40,000 pages/day	40,000 pages/day	
Supported Operating Systems	Windows 10, 8, 7		

Accessories: DocuMate 4700 flatbed scanner, Pre- & Post-Scan Imprinter

For more information about the Xerox line of scanners, visit www.xeroxscanners.com

©2020 Xerox Corporation. All rights reserved. Xerox®, DocuMate®, FreeFlow Makeready® and iGen® are registered trademarks of Xerox Corporation in the United States and other countries, and are used under license from Xerox Corporation. Visioneer® is an authorised trademark licensee of Xerox®. Visioneer® and Visioneer OneTouch® are trademarks of Visioneer, Inc. All other trademarks are the property of their respective owners and are hereby acknowledged. Prices, features, specifications, capabilities, appearance and availability of Xerox® products and services are subject to change without notice. 04/20 BR29525-UK